

SPE 151279

# A New Buckling Severity Index to Quantify Failure and Lock-up Risks in Highly Deviated Wells



Menand S., SPE, DrillScan US Inc.

## Abstract

Buckling of tubulars inside wellbore has been the subject of many researches and articles in the past. Evidences in the laboratory and in the field have shown that existing buckling criteria (sinusoidal and helical buckling) have to be challenged, as they fail to predict the onset of buckling phenomenon in complex or unconventional wells drilled today. Indeed, existing buckling criteria assume generally that the wellbore is idealistically perfect without any dog legs. Recent advancements in drillstring mechanics modelling has demonstrated that dog legs, friction and rotation affect greatly the buckling phenomenon. Buckling does not imply necessarily failure neither lock-up, but indicates the onset of a condition that may generate poor drilling performance that could lead to failure or lock-up. In this paper, one proposes a new buckling severity index that quantifies the severity of the buckling phenomenon enabling drilling engineers to take appropriate decision.

A fully validated numerical buckling model has been used to derive a new buckling severity index based on the risk of drill pipe failure or lock-up. This index ranges from 1 for acceptable buckling condition with low risk of failure, to index 4 for severe buckling with high risk of failure or lock-up. This new buckling severity index has been compared to well-known sinusoidal and helical buckling loads in a few case studies, and demonstrates that past buckling criteria should be used very cautiously.

This paper proposes an update of past conventional buckling criteria in recommending a new buckling severity index that enables to quantify the risks of failure or lock-up in unconventional and deviated wells. These new results presented in this paper should improve significantly well planning and operational procedures to drill and operate increasing complex wells.

Copyright 2012, Society of Petroleum Engineers

This paper was prepared for presentation at the SPE Deepwater Drilling and Completions Conference held in Galveston, Texas, USA, 20–21 June 2012. This paper was selected for presentation by an SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of SPE copyright.



*[Visit OnePetro to read the full paper](#)*