

IADC/SPE 151283

# PDC Bit Steerability Modeling and Testing for Push-the-bit and Point-the-bit RSS

Menand S., Simon C., Gaombalet J., Macresy L., DrillScan, Gerbaud L., Ben Hamida M., Mines ParisTech, Amghar Y., Total, Denoix H., Schlumberger, Cuiller B., Sinardet H., Varel



## Abstract

The footage drilled with rotary steerable systems (RSS) has increased significantly these last few years, due notably to the highly complex wells drilled today. Moreover, high requirements about borehole quality are needed to optimize drilling performances, running completion tools or increase the quality of formation evaluation.

Rotary steerable systems can be classified in two types according to the steering mechanism: point-the-bit and push-the-bit. Whatever the type of steering mechanism, both tilt and side force are applied on the bit. Although bit tilt is predominant in point-the-bit system, bit side force is the main factor that affects hole deviation in push-the-bit system. There have been many controversies in the scientific and industrial community regarding the deviation mechanisms involved in these two systems. To react to this controversy, a full-scale drilling bench has been developed to test drill bits in push-the-bit, point-the-bit or hybrid push-point mode. This new facility enables to apply any coupled tilt-side force on the bit to reproduce the RSS mechanisms.

This paper is intended to show results of this experimental campaign. First, the role of the side force and of the bit tilt in the deviation process have been fully differentiated and measured. Then, these results demonstrate that the bit steerability for a same given side force is strongly affected by the tilt applied on it. At last, one shows that borehole quality is not only affected by the bit design itself but also by the tilt-side force combination. These experimental results presented in this paper have been validated with a software that enables to reproduce the hole deviation every inch drilled. The results of this paper should also contribute to improve bits selection for RSS in order to drill a smooth and uniform borehole.

Copyright 2012, IADC/SPE Drilling Conference and Exhibition

This paper was prepared for presentation at the 2012 IADC/SPE Drilling Conference and Exhibition held in San Diego, California, USA, 6–8 March 2012. This paper was selected for presentation by an IADC/SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the International Association of Drilling Contractors or the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the International Association of Drilling Contractors or the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the International Association of Drilling Contractors or the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of IADC/SPE copyright.



*[Visit OnePetro to read the full paper](#)*