

SPE-188865-MS

# Using Aluminum Drill Pipe with Axial Oscillation Tools to Significantly Improve Drilling Performance



K. Mills and S. Menand, DrillScan US Inc.; R. Grissom, Otto Fuchs

## Abstract

Aluminum drill pipe has already been proven as a viable alternative to steel drill pipe when drilling long horizontal wells thanks to its lighter weight that does not compromise resistance to yield and buckling. At the same time, the development of unconventional wells has seen the deployment of numerous technologies to further improve the performance and increase the lateral section to reduce costs. An operator has recently and successfully tested a new aluminum drill pipe with an axial oscillation tool to push further the limits of the drilling system.

This paper presents the key findings of the case study using a mixed aluminum-steel string combined with an axial oscillation tool. First, the innovative drill pipe design is presented, followed by lessons learned during rig operations regarding pipe handling practices, rig compatibility and pipe inspection. Then, results of the drilling simulations performed during the well planning phase are presented. This modeling led to an optimum drill string design associating the steerable mud motor assembly, aluminum drill pipe, axial oscillation tool and steel drill pipe. The number and placement of aluminum drill pipe along the string was key to reducing friction and improving weight transfer between the bit and the axial oscillation tool.

Through extensive modeling and field data interpretation, this paper presents the comparison of the overall drilling performance between steel only and aluminum-steel drill pipe strings and provides metrics in terms of weight transfer and rate of penetration improvement. This innovative and promising drill string design opens the doors to set new limits in terms of horizontal departure.

Copyright 2017, Society of Petroleum Engineers

This paper was prepared for presentation at the Abu Dhabi International Petroleum Exhibition & Conference held in Abu Dhabi, UAE, 13-16 November 2017. This paper was selected for presentation by an SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of SPE copyright.



*[Visit OnePetro to read the full paper](#)*